



HP12-110DTS COLD WATER CLEANER WITH DELAYED TOTAL STOP

SPECIFICATIONS

1650 P.S.I. (110 Bar) Pump Pressure
2700 P.S.I. Turbo Pressure (Optional)
12 Litres per minute Pump Volume
240 Volt 3 H.P. Electric Motor
1450 RPM Industrial Machine
15 AMP Single Phase Power

STANDARD EQUIPMENT

Delayed Total Stop System
10 Metres High Pressure Hose
Chemical Injector and 5 L Bottle
Insulated On/Off Pistol Assembly
Single Lance with Adjustable Multireg Nozzle
High and Low Pressure Mode
Operators and Parts Manuals

<u>FEATURES</u>	<u>BENEFITS</u>
Interpump with Ceramic Pistons and Brass Head	→ Anodised crankcase and oversized bearings → Longer pump life, non-corrosive pump head
Delayed Total Stop	→ Puts machine in suspense when not used
Inlet Water Filter	→ Stops debris from scoring pistons and seals
Pressure Gauge	→ Easily monitor pump performance
Powder Coated Zinc Annealed Chassis	→ Resistant to corrosion
Heavy Duty Insulated Pistol Assembly	→ Designed for heavy duty industrial use
Australian designed, manufactured and tested	→ Built for tough Australian working conditions