



SPACE HEATERS



# IP32

Indirect Fired Diesel Heater



### Specifications

- ⇒ Heat output 32 kW / 109,188 BTU/h
- ⇒ 42 L fuel tank
- ⇒ 2.7 kg/h fuel consumption
- ⇒ 240 V 10 amp plug
- ⇒ 3M minimum safe distance
- ⇒ 1150 m<sup>3</sup>/h Airflow
- ⇒ 48 kg (empty)

### Standard Equipment

- ⇒ Robust compact design
- ⇒ All Steel constructed tank, body & trolley
- ⇒ Automatic Ignition
- ⇒ Large fuel tank with drain plug
- ⇒ Ergonomic handle & solid wheels
- ⇒ Chimney exhaust connection

Features	Benefits
Internal stainless steel burner combustion chamber	Allows external surface to stay cool
Safety Thermostat & Flame-out control	Shuts down when internal fault is detected
Built-in room thermostat with LED display	Efficient and consistent room temperature control whilst reducing the fuel consumption
Low Maintenance burner system	Lowering maintenance costs
Socket for optional accessory connection	Allows for an additional thermostat or automatic timer to be used

For more information, please visit our website

[spitwater.com.au](http://spitwater.com.au)

**TOUGH + READY**  
CREATED BY OTTICO