

SW2021S

Hot/Cold Water Cleaner



Specifications

- ⇒ 200 bar (2900 psi) pump pressure
- ⇒ 289 bar (4200 psi) EWP pressure (optional)
- ⇒ 21 Litres Per Minute pump volume
- ⇒ 415 V 10 hp Electric motor
- ⇒ 1450 rpm low speed pump
- ⇒ 20 amp plug 3 phase
- ⇒ Temperatures up to 90°
- ⇒ Heavy duty machine

Standard Equipment

- ⇒ 10 Metres high pressure hose
- ⇒ Insulated on/off pistol assembly
- ⇒ Double lance assembly
- ⇒ High & Low pressure mode
- ⇒ Adjustable chemical injector with bottle
- ⇒ Bypass shutdown timer
- ⇒ **Stainless steel heating coil**
- ⇒ Operating and Maintenance manual

Features

Interpump with ceramic pistons and brass head

Water cooling tank

Inlet water filter

3 Stage powder coated zinc annealed chassis

Adjustable thermostat for hot water temperature control

Bypass shutdown timer

Stainless steel heating coil

Benefits

Non-corrosive pump head to extend pump life and reduced maintenance costs

Reduces potential damage to the pump in bypass

Stops debris from scoring pistons and seals

Resistant to corrosion

Set the ideal temperature for any application

Increases life of the machine by shutting down when not in use

Corrosion resistance extends the life of the heating coil

For more information,
please visit our website

spitwater.com.au