



PRESSURE CLEANERS



Made in Australia
SINCE 1982

HP251AE

Cold Water Cleaner



Specifications

- ⇒ 250 bar (3626 psi) pump pressure
- ⇒ 310 bar (4496 psi) EWP pressure (optional)
- ⇒ 15 Litres Per Minute pump volume
- ⇒ 13 hp Honda petrol motor
- ⇒ 1450 rpm low speed pump
- ⇒ Electric start
- ⇒ Heavy duty machine

Standard Equipment

- ⇒ 10 Metres high pressure hose
- ⇒ Insulated on/off pistol assembly
- ⇒ Double lance assembly
- ⇒ High and Low pressure mode
- ⇒ Adjustable chemical injector with bottle
- ⇒ Operating and Maintenance manual

Features	Benefits
Interpump with ceramic pistons and brass head	Non-corrosive pump head to extend pump life and reduced maintenance costs
Oz-tuff belt drive	15% more power available than a gearbox and no more gearbox oil leaks (maintenance free)
Water cooling tank	Reduces potential damage to the pump in bypass
Inlet water filter	Stops debris from scoring pistons and seals
Pressure gauge	Easily monitor pump performance
3 Stage powder coated zinc annealed chassis and frame with lifting hook and 4 pneumatic wheels	Resistant to corrosion and greater manoeuvrability over tough terrain

For more information,
please visit our website

spitwater.com.au

TOUGH + READY
CREATED BY **OTTICO**