

# SPITWATER

PRESSURE CLEANERS



Made in Australia  
SINCE 1962

## HC12-180P

Petrol Cold Water Cleaner

**DDD**  
MEDIUM DUTY

### Ergonomic Handle

Longer handle positioned at the perfect height for safe operation and easy manoeuvrability.



### Accessory Holder

Additional accessories can be securely stored on the machine.

### Robust Frame

Steel powder-coated frame protects the pump from damage during operation and transit, providing optimum durability.

### Honda Engine with Anti-vibration Mounts

Easy, reliable, 6.5 hp genuine Honda industrial petrol engine with 3-year warranty. Equipped with mounts that absorb engine vibrations for better performance and longer machine life.

### Gun & Lance Holder

Made from powder-coated steel, providing easy access during operation. Also secures the lance off the ground when not in use, eliminating the chance of dirt and debris blocking the nozzle.

### Hose Carrier

Powder-coated steel bracket keeps hose tidy when not in use.



**TOUGH  
+ READY**

# HC12-180P

The HC12-180P has been redesigned by our team with the customer in mind. It is manufactured from the ground up, at the Albury factory, delivering ergonomically enhanced tough and ready pressure cleaner solution. This medium duty model is rated for commercial use and is fitted with a genuine Honda GX200 engine. It is paired with an Interpump Model EVO 1 crankshaft, piston pump for ultimate reliability. With water pressure of 180 Bar (2610 psi) and flow of 12 L/min, it delivers excellent cleaning power for use in transport and logistics, property maintenance, building site clean-up and other general cleaning jobs to be done.

## Technical Specifications

Pump		Engine	
Model	Interpump EVO 1 Model E1E1812CV	Model	6.5 hp Honda (GX200)
Pump Pressure	180 Bar (2610 psi)	Type	4-Stroke single cylinder, OHV
Turbo Pressure	255 Bar (3698 psi)	Fuel Type	Petrol, Unleaded
Pump Flow Rate	12 L/min	Fuel Capacity	3.1 Litres
Speed	3400 rpm	<b>Dimensions &amp; Weight</b>	
Max Inlet Temp	40°C	Frame Structure	Heavy duty zinc-annealed & powder coated steel tubing
Oil Type	15W-40	Dimensions	460mm (L) x 505mm (W) x 940mm (H)
Capacity	0.25 Litres	Weight	33 kgs
Performance		<b>Warranty</b>	
Duty Cycle	Medium Duty	Unit / Pump	12 months
Usage Frequency	Medium Commercial: up to 4 hours a day continuous	Engine	36 months (commercial use)

## Ordering Information

Model Number	Description
HC12-180P	<b>Petrol Engine Powered Cold Water Medium Duty Pressure Cleaner</b> Supplied with an 8m, 3/8 inch diameter, single wire braid high pressure hose, commercial grade, insulated trigger gun with safety lock, commercial grade single lance assembly with quick release coupling, 4-way adjustable spray nozzle (hi-lo pressure, 0-40 degrees spray angle) and adjustable chemical injector complete with chemical suction hose and strainer.

## Optional Accessories

Model Number	Description
PA26105000	<b>High Pressure Swivel</b> to eliminate unwanted twisting of the hose.
SWA501	<b>Turbo Lance</b> to reduce cleaning time by increasing washing effect.
SWA551	<b>Foamer with 1 L Tank</b> for detergent application. Foamed detergent adheres to surfaces more effectively. It offers longer contact time, provides even coverage lifting dirt and grime for ultimate cleaning performance.
GPDFSCP12-KIT	<b>12" Flat Surface Cleaner</b> complete with 340mm lance to reduce cleaning time of flat surfaces such as driveways and rooves.
46602/20N	<b>20m Extension Hose</b> complete with M22 nipple to extend cleaning reach.

The manufacturer reserves the right to modify designs, features and technical data without notice.

