

**PRESSURE CLEANERS** 



| SSA5-200SPE<br>Hot/Cold Water Cleaner        |  |
|--|--|
| Specifications                               | Standard Equipment                               |
| ᅌ 200 bar (2900 psi) pump pressure           | → Stainless steel heating coil                   |
| 280 bar (4061 psi) Turbo pressure (optional) | 🗘 Water cooling tank                             |
| 15 L/min pump water volume                   | 10 Metre high pressure hose                      |
| ᅌ 13 hp Honda electric start petrol engine   | Insulated on/off pistol assembly                 |
| ᅌ 1450 rpm low speed pump                    | Dual lance with high / low pressure valve        |
| 12 V Diesel burner system                    | Adjustable chemical injector with 10 L container |

- Temperatures up to 90°
- ↔ Heavy duty machine

- ↔ E-stop and battery isolator
- **Operating and Maintenance Manual**

## Benefits

| Features  | Benefits   |
|---|--|
| Interpump with ceramic pistons and brass head   | Longer pump life and reduced maintenance costs   |
| Water cooling tank and low level water switch   | Protects the pump from overheating in by-pass (trigger closed) mode and prevents machine running dry |
| Stainless Steel, seamless heating coil  | Corrosion resistant for longer heating coil life   |
| 3 Stage zinc annealed, and powder coated chassis and frame with forklift lifting points | Resistant to corrosion and able to be moved safely and easily  |
| Spitwater 'Oz-Tuff' belt drive  | Efficient and reliable transfer of power, needs less power to drive, uses less fuel                  |
| Emergency stop and battery isolator   | Enhanced operator safety and machine protection  |
| Pressure gauge and hour meter   | Easy monitoring of machine performance   |

For more information, please visit our website



