

NEW
PRODUCTS

DIESEL INDUSTRIAL PORTABLE HEATERS & DRYERS

- ▶ Direct and indirect fired models
- ▶ Designed and manufactured in Italy for SPITWATER
- ▶ SPITWATER superior quality and reliability
- ▶ Extensive range of replacement parts and accessories
- ▶ Exceptional SPITWATER after sales care Australia-wide

JETFIRE®



INDIRECT FIRED INDUSTRIAL PORTABLE HEATERS & DRYERS

JETFIRE®



IP32 & IP110

Specifically designed to provide an instant, reliable and efficient clean, fume-free source of heat allowing fumes to be exhausted through a separate chimney. Ideal for places where there is limited ventilation or where people are present.

APPLICATIONS

Warehouses, workshops, garages, factories, marquees and other temporary structures, transport terminals, breeding sheds, animal shelters and greenhouses.



IP32

FEATURES

- ▶ Robust, compact design
- ▶ High efficiency combustion
- ▶ Stainless steel combustion chamber
- ▶ Socket for connection to optional accessories (thermostat, timer, etc)
- ▶ Electronic safety shutdown on flame/fan failure and overheat
- ▶ Fuel tank drain plug
- ▶ Large fuel tank for longer run times

SPECIFICATIONS

Model	IP32
Fuel type	Diesel
Heat output	28.9 kW / 98815 BTU/h
Air flow	1150 m ³ /h
Fuel consumption	2.7 kg/h
Electrical supply	230V / 1 phase / 50Hz
Connected load	370 W
Fuel tank capacity	42 L
Dimensions L x W x H	1215 x 440 x 670 mm
Weight	48 kg

*Not suitable for domestic use and when being used in an enclosed space, adequate fresh air ventilation must be provided. The manufacturer reserves the right to modify design features and technical data without notice.

INDIRECT FIRED INDUSTRIAL PORTABLE HEATERS & DRYERS

JETFIRE®



IP110

FEATURES

- ▶ Robust, compact design
- ▶ High efficiency combustion
- ▶ Stainless steel combustion chamber
- ▶ Socket for connection to optional accessories (thermostat, timer, etc)
- ▶ Electronic safety shutdown on flame/fan failure and overheat
- ▶ Fuel tank drain plug
- ▶ Large fuel tank for longer run times
- ▶ Two stage heat selection
- ▶ Inlet air recirculation
- ▶ Dedicated switch to swap from Winter Heating to Summer Ventilation mode

SPECIFICATIONS

Model	IP 110
Fuel type	Diesel
Heat output: Low - High	71.2 kW / 244941 BTU/h - 99.02 kW / 340619 BTU/h
Air flow	5300 m ³ /h
Fuel consumption: Low - High	6.33 - 9.278 kg/h
Electrical supply	230V / 1 phase / 50Hz
Connected load	1820 W
Fuel tank capacity	135 L
Dimensions L x W x H	1918 x 731 x 1220 mm
Weight	149 kg

*Not suitable for domestic use and when being used in an enclosed space, adequate fresh air ventilation must be provided. The manufacturer reserves the right to modify design features and technical data without notice.

DIRECT FIRED INDUSTRIAL PORTABLE HEATERS & DRYERS



DP65 & DP105

Specifically designed to provide an instant, reliable and efficient source of heat to the industrial, agricultural, commercial and construction sectors.

FEATURES

- ▶ Robust, compact design
- ▶ High efficiency combustion
- ▶ Stainless steel combustion chamber
- ▶ Socket for connection to optional accessories (thermostat, timer, etc)
- ▶ Electronic safety shutdown on flame/fan failure and overheat
- ▶ Fuel tank drain plug
- ▶ Large fuel tank for longer run times

APPLICATIONS

Warehouses, workshops, garages, factories, transport terminals, breeding sheds, greenhouses, drying and curing of materials.



SPECIFICATIONS

Model	DP65	DP105
Fuel type	Diesel	Diesel
Heat output	69.3 kW / 237067 BTU/h	111.1 kW / 380331 BTU/h
Air flow	2500 m ³ /h	4600 m ³ /h
Fuel consumption	5.48 kg/h	8.85 kg/h
Electrical supply	230V / 1 phase / 50Hz	230V / 1 phase / 50Hz
Connected load	598 W	1170 W
Fuel tank capacity	65 L	105 L
Dimensions L x W x H	1200 x 555 x 860 mm	1492 x 670 x 1005 mm
Weight	58 kg	86 kg